

MATERIAL SAFETY DATA SHEET

IN CASE OF EMERGENCY CALL: CHEMTREC 1-800-424-9300 CONTACT ONLY IN CASE OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

PRODUCT NAME: **ECOPOXY RESIN**

COMPANY NAME: ECOPOXY INC.
Box 220, Morris, MB R0G 1K0
1-855-326-7699 www.ecopoxy.ca

1. INGREDIENTS:

REACTION PRODUCTS OF EPICHLOROHYDRIN AND BISPHENOL A	<55%
ALKYL GLYCIDYL ETHER	<15%
FLORA MICROBIOLE OIL	<30%

THIS DOCUMENT IS PREPARED PURSUANT TO THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) IN ADDITION, OTHER SUBSTANCES NOT HAZARDOUS PER THIS OSHA STANDARD MAY BE LISTED. WHERE PROPRIETARY INGREDIENT SHOWS, THE IDENTITY MAY BE MADE AVAILABLE AS PROVIDED IN THIS STANDARD.

2. PHYSICAL DATA

BOILING POINT:	NOT APPLICABLE
VAPOR PRESSURE:	NOT APPLICABLE
VAPOR DENSITY:	NOT APPLICABLE
SOL. IN WATER:	NONE
SPECIFIC GRAVITY:	1.08-1.10
APPEARANCE:	CLEAR COLORED LIQUID
ODOR:	FAINT EPOXY ODOR

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 245°F	METHOD USED: PMCC
FLAMMABLE LIMITS:	LFL: NOT APPLICABLE
	UFL: NOT APPLICABLE
EXTINGUISHING MEDIA:	FOAM, CO ₂ , DRY CHEMICAL
FIRE & EXPLOSION HAZARDS:	NONE
FIRE-FIGHTING EQUIPMENT:	USE A POSITIVE PRESSURE, SELF-CONTAINED BREATHING APPARATUS.

4. REACTIVITY DATA

STABILITY: (CONDITIONS TO AVOID) EXCESS HEATING OVER LONG PERIODS OF TIME DEGRADES THE RESIN.

INCOMPATIBILITY: (SPECIFIC MATERIALS TO AVOID) BASE
UNCONTROLLED CONDITIONS: STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: THE BY-PRODUCTS EXPECTED IN INCOMPLETE PYROLYSIS OR COMBUSTION OF EPOXY RESINS ARE MAINLY PHENOLICS, CARBON MONOXIDE AND WATER. THE THERMAL DECOMPOSITION PRODUCTS OF EPOXY RESINS THEREFORE SHOULD BE TREATED AS POTENTIALLY HAZARDOUS SUBSTANCES, AND APPROPRIATE PRECAUTIONS SHOULD BE TAKEN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR BY ITSELF BUT, MASSES MORE THAN 500 GRAMS OF PRODUCT PLUS ALIPHATIC AMINE WILL CAUSE IRREVERSIBLE POLYMERIZATION WITH CONSIDERABLE HEAT BUILD UP.

MATERIAL SAFETY DATA SHEET

MSDS

ECOPOXY RESIN

PAGE 2

5. ENVIRONMENTAL AND DISPOSAL INFORMATION

ACTION TO TAKE FOR SPILL AND LEAKS: SOAK UP IN ABSORBENT MATERIAL AND COLLECT IN SUITABLE CONTAINERS. RESIDUAL MAY BE REMOVED USING STEAM OR HOT SOAPY WATER.

DISPOSAL METHOD: BURN IN ADEQUATE INCINERATOR OR BURY IN AN APPROVED LANDFILL; IN ACCORDANCE WITH LOCAL, PROVINCIAL, AND FEDERAL REGULATIONS.

6. HEALTH HAZARD DATA

EYES: MINOR TRANSIENT IRRITATION. NO CORNEAL INJURY LIKELY.

SKIN CONTACT: MAY CAUSE ALLERGIC SKIN REACTION IN SUSCEPTIBLE INDIVIDUALS. PROLONGED EXPOSURE NOT LIKELY TO CAUSE SIGNIFICANT SKIN IRRITATION. REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION.

SKIN ABSORPTION: A SINGLE PROLONGED EXPOSURE MAY RESULT IN THE MATERIAL BEING ABSORBED IN HARMFUL AMOUNTS. THE LD₅₀ FOR SKIN ABSORPTION IN RABBITS IS 20,000 mg/kg

INGESTION: THE ORAL LD₅₀ FOR SOYBEAN OIL IS 23g/kg ORAL (RAT). THE LC₅₀ FOR SOYBEAN OIL IS 240mg/L. NO HAZARDS ANTICIPATED FROM INGESTION INCIDENTAL TO INDUSTRIAL EXPOSURE.

INHALATION: VAPORS ARE UNLIKELY DUE TO PHYSICAL PROPERTIES. NOT A PROBLEM UNLESS HEATED TO A HIGH TEMPERATURE.

SYSTEMIC & OTHER EFFECTS: EXCEPT FOR SKIN SENSITIZATION, REPEATED EXPOSURES TO LOW MOLECULAR WEIGHT EPOXY RESINS OF THIS TYPE ARE NOT ANTICIPATED TO CAUSE ANY SIGNIFICANT ADVERSE EFFECTS. A POORLY CHARACTERIZED SAMPLE OF LOW MOLECULAR WEIGHT EPOXY RESIN OF THIS TYPE HAS BEEN REPORTED TO PRODUCE SKIN CANCER IN A HIGHLY SENSITIVE STRAIN OF MICE. HOWEVER, HIGH LEVELS OF IMPURITIES COMPROMISE THE VALIDITY OF THE FINDINGS. EPOXY RESIN THAT IS REPRESENTATIVE OF CURRENT MANUFACTURING PROCESSES IS NOT BELIEVED TO BE A CANCER HAZARD TO HUMANS. RESULTS OF MUTAGENICITY TESTS IN ANIMALS HAVE BEEN NEGATIVE. HAS BEEN SHOWN TO BE NEGATIVE IN SOME VITRO MUTAGENICITY TESTS AND POSITIVE IN OTHERS.

7. FIRST AID

EYES: IMMEDIATE AND CONTINUOUS IRRIGATION WITH FLOWING WATER FOR AT LEAST 15 MINUTES IS A GOOD SAFETY PRACTICE.

SKIN: CONTACT WILL PROBABLY CAUSE NO MORE THAN IRRITATION. WASH OFF IN FLOWING WATER OR SHOWER. WASH CLOTHING BEFORE REUSE.

INGESTION: LOW IN TOXICITY. NO ADVERSE EFFECTS ANTICIPATED BY THIS ROUTE OF EXPOSURE INCIDENTAL TO PROPER INDUSTRIAL HANDLING.

INHALATION: REMOVE TO FRESH AIR IF EFFECTS OCCUR. CONSULT MEDICAL PERSONNEL.
NOTE TO PHYSICIAN: NO SPECIFIC ANTIDOTE. SUPPORTIVE CARE. TREATMENT BASED ON JUDGEMENT OF THE PHYSICIAN IN RESPONSE TO REACTIONS OF THE PATIENT.

MATERIAL SAFETY DATA SHEET

MSDS

ECOPOXY RESIN

PAGE 3

8. HANDLING

EXPOSURE GUIDELINE(S): NONE ESTABLISHED.
VENTILATION: GOOD ROOM VENTILATION USUALLY ADEQUATE FOR MOST OPERATIONS.
RESPIRATORY PROTECTION: NONE NORMALLY NEEDED
SKIN PROTECTION: FOR BRIEF CONTACT, NO PRECAUTIONS OTHER THAN CLEAN BODY-COVERING CLOTHING SHOULD BE NEEDED. USE IMPERVIOUS GLOVES WHEN PROLONGED OR FREQUENTLY REPEATED CONTACT COULD OCCUR.
EYE PROTECTION: USE CHEMICAL GOGGLES.

9. ADDITIONAL INFORMATION

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
PRACTICE GOOD CAUTION AND PERSONNEL CLEANLINESS TO AVOID SKIN AND EYE CONTACT.
AVOID BREATHING VAPORS OF HEATED MATERIAL.

10. NFPA HAZARD RATING

4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT

HEALTH: 1
FIRE: 1
REACTIVITY: 0
SPECIFIC:

11. REGULATORY INFORMATION: STATUS ON SUBSTANCE LISTS

THE CONCENTRATIONS SHOWN IN THIS DOCUMENT ARE MAXIMUM OR CEILING LEVELS (WEIGHT %) TO BE USED FOR REGULATIONS. TRADE SECRETS ARE INDICATED BY "TS".

MATERIAL SAFETY DATA SHEET

MSDS

ECOPOXY RESIN

PAGE 4

FEDERAL EPA

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (CERCLA)

REQUIRES NOTIFICATION OF THE NATIONAL RESPONSE CENTER OF RELEASE OF QUANTITIES OF HAZARDOUS SUBSTANCES EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITIES (RQ'S) IN 40 CFR 302.4. COMPONENTS PRESENT IN THIS PRODUCT AT LEVEL WHICH COULD REQUIRE UNDER THE STATUTE ARE:

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT	RQ
NONE			

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III SECTIONS (301-304) REQUIRE EMERGENCY PLANNING BASED ON THRESHOLD PLANNING QUANTITIES (TPQS) AND RELEASE REPORTING BASED ON REPORTABLE QUANTITIES (RQS) IN 40 CFR 355. COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL WHICH COULD REQUIRE REPORTING UNDER THIS STATUTE ARE:

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT
NONE		

SECTIONS (311-312) REQUIRE PRODUCTS BE REVIEWED AND APPLICABLE EPA HAZARD DEFINITIONS BE IDENTIFIED AND MADE KNOWN.

EPA HAZZARD CLASSIFICATIONS

ACUTE HAZARD	CHRONIC HAZARD	FIRE HAZARD	PRESSURE HAZARD	REACTIVE HAZARD
NO	NO	NO	NO	NO

SECTION (313) REQUIRES SUBMISSION OF ANNUAL REPORTS OF RELEASE OF TOXIC CHEMICALS THAT APPEAR IN 40 CFR 372 (FOR SARA 313). THIS INFORMATION MUST BE INCLUDED IN ALL MSDS'S THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL. COMPONENTS PRESENT IN THIS PRODUCT AT LEVEL WHICH COULD REQUIRE REPORTING UNDER THE STATUE ARE:

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT
NONE		

IF YOU ARE UNSURE IF YOU MUST REPORT MORE INFORMATION, CALL THE EPA EMERGENCY PLANNING AND RIGHT-TO-KNOW HOT LINE: 1-800-535-0202 OR 1-202-479-2449.

TOXIC SUBSTANCES CONTROL ACT (TCSA)

THE COMPONENTS OF THIS PRODUCT ARE CONTAINED ON THE CHEMICAL SUBSTANCE INVENTORY LIST.

OTHER REGULATORY INFORMATION

D.O.T. SHIPPING NAME: NOT REGULATED BY D.O.T.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY EXPRESSED OR IMPLIED IS MADE. MANUFACTURER URGES SUPPLIERS AND USERS OF THIS PRODUCT TO EVALUATE IT'S SUITABILITY AND COMPLIANCE WITH LOCAL REGULATION.

MATERIAL SAFETY DATA SHEET

IN CASE OF EMERGENCY CALL: CHEMTREC 1-800-424-9300 CONTACT ONLY IN CASE OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

PRODUCT NAME: **ECOPOXY HARDENER**

COMPANY NAME: ECOPOXY INC.
Box 220, Morris, MB R0G 1K0
1-855-326-7699 www.ecopoxy.ca

1. INGREDIENTS

ISOPHORONE DIAMINE	<35%
BENZYL ALCOHOL	<30%
1, 3-BENZENEDIMETHANAMINE	<20%
FLORA MICROBILE OIL	<15%

THIS DOCUMENT IS PREPARED PURSUANT TO THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) IN ADDITION, OTHER SUBSTANCES NOT HAZARDOUS PER THIS OSHA STANDARD MAY BE +LISTED. WHERE PROPRIETARY INGREDIENT SHOWS, THE IDENTITY MAY BE MADE AVAILABLE AS PROVIDED IN THIS STANDARD.

2. PHYSICAL DATA

BOILING POINT:	>150°C @ 5 mm HG
VAPOR PRESSURE:	.02mmHG@20°C,68°F
VAPOR DENSITY:	5.88
SOL. IN WATER:	MODERATELY SOLUBLE
SP. GRAVITY:	1.0-1.01
APPEARANCE:	PALE STRAW COLORED LIQUID
ODOR:	AMINE ODOR

3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	213°F	METHOD USED:	PMCC		
FLAMMABLE LIMITS:		LFL:	NOT DETERMINED	UFL:	NOT DETERMINED
EXTINGUISHING MEDIA:	WATER FOG, ALCOHOL FOAM, CO2, DRY CHEMICAL				
FIRE & EXPLOSION HAZARDS:	USE FULL PROTECTIVE CLOTHING				
FIRE-FIGHTING EQUIPMENT:	USE A POSITIVE PRESSURE, SELF-CONTAINED BREATHING APPARATUS.				

4. REACTIVITY DATA

STABILITY: (CONDITIONS TO AVOID) CAN REACT STRONGLY WITH EPOXY RESINS AT ELEVATED TEMPERATURES.

INCOMPATIBILITY: (SPECIFIC MATERIALS TO AVOID) EPOXY RESINS UNDER UNCONTROLLED CONDITIONS AND STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: NITROGEN OXIDES WHEN BURNED

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

MATERIAL SAFETY DATA SHEET

MSDS ECOPOXY HARDENER **PAGE 2**

5. ENVIRONMENTAL AND DISPOSAL INFORMATION

ACTION TO TAKE FOR SPILL AND LEAKS:

LARGE SPILL: DIKE UP AND PUMP INTO APPROPRIATE CONTAINERS.

SMALL SPILL: USE NONCOMBUSTIBLE ABSORBENT MATERIAL (SAND) AND SHOVEL INTO SUITABLE CONTAINERS.

DISPOSAL METHOD: LARGE QUANTITIES SHOULD BE RECOVERED. COLLECT SMALL QUANTITIES IN WASTE METAL DRUMS AND SEAL FOR REMOVAL TO AN APPROVED LANDFILL OR INCINERATE IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

6. HEALTH HAZARD DATA

EYES: MAY CAUSE SEVERE IRRITATION WITH CORNEAL INJURY, WHICH MAY RESULT IN PERMANENT IMPAIRMENT OF VISION, EVEN BLINDNESS. VAPORS MAY IRRITATE EYES.

SKIN CONTACT: MAY CAUSE SEVERE INJURY TO SKIN FOLLOWING PROLONGED OR REPEATED CONTACT AND MAY CAUSE SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

SKIN ABSORPTION: A SINGLE PROLONGED EXPOSURE MAY RESULT IN THE MATERIAL BEING ABSORBED IN HARMFUL AMOUNTS. THE LD₅₀ FOR SKIN ABSORPTION HAS NOT BEEN DETERMINED.

INGESTION: SINGLE DOSE ORAL TOXICITY IS LOW. THE ORAL LD₅₀ FOR FLORA OIL IS 23g/kg Oral Rat. THE LC₅₀ FOR FLORA OIL IS 240mg/L. INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION OR ULCERATION. INGESTION MAY CAUSE BURNS OF MOUTH AND THROAT.

INHALATION: MAY CAUSE RESPIRATORY SENSITIZATION OR ASTHMA IN SUSCEPTIBLE INDIVIDUALS. EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT.

SYSTEMIC & OTHER EFFECTS: RESULTS OF IN VITRO ("TEST TUBE") MUTAGENICITY TESTS HAVE BEEN NEGATIVE.

7. FIRST AID

EYES: IMMEDIATE AND CONTINUOUS IRRIGATION WITH FLOWING WATER FOR AT LEAST 30 MINUTES IS REQUIRED. PROMPTLY SEEK MEDICAL ATTENTION

SKIN: IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING, PREFERABLY UNDER A SAFETY SHOWER. SEEK MEDICAL ATTENTION IMMEDIATELY. AVOID PROLONGED OR REPEATED CONTACT TO SKIN. WASH THOROUGHLY AFTER HANDLING.

INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE AMOUNTS OF WATER OR MILK IF AVAILABLE. **NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.** TRANSPORT TO MEDICAL FACILITY IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR IF EFFECTS OCCUR. CONSULT A PHYSICIAN.

NOTE TO PHYSICIAN: CORROSIVE, MAY CAUSE STRICTURE. IF LAVAGE IS PERFORMED, SUGGEST ENDOTRACHEAL AND/OR ESOPHAGOSCOPIC CONTROL. IF BURN IS PRESENT, TREAT AS ANY THERMAL BURN, AFTER DECONTAMINATION. NO SPECIFIC ANTIDOTE. SUPPORTIVE CARE. TREATMENT BASED ON JUDGMENT OF THE PHYSICIAN IN RESPONSE TO REACTIONS OF PATIENT.

MATERIAL SAFETY DATA SHEET

MSDS

ECOPOXY HARDENER

PAGE 3

8. HANDLING PRECAUTIONS

EXPOSURE GUIDELINE(S): NONE ESTABLISHED.

VENTILATION: CONTROL AIRBORNE CONCENTRATION BELOW THE EXPOSURE GUIDELINE. USE ONLY WITH ADEQUATE VENTILATION. LOCAL EXHAUST VENTILATION MAY BE NECESSARY FOR SOME OPERATIONS.

RESPIRATORY PROTECTION: ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW THE EXPOSURE GUIDELINE. WHEN RESPIRATORY PROTECTION IS REQUIRED FOR CERTAIN OPERATIONS, USE AN APPROVED AIR-PURIFYING RESPIRATOR.

SKIN PROTECTION: USE PROTECTIVE CLOTHING IMPERVIOUS TO THIS MATERIAL. SELECTION OF SPECIFIC ITEMS SUCH AS GLOVES, BOOTS, APRON, OR FULL-BODY SUIT WILL DEPEND ON OPERATION. SAFETY SHOWER SHOULD BE LOCATED IN IMMEDIATE WORK AREA. REMOVE CONTAMINATED CLOTHING IMMEDIATELY, WASH SKIN AREA WITH SOAP AND WATER AND LAUNDRY CLOTHING BEFORE REUSE. CONTAMINATED LEATHER ITEMS, SUCH AS SHOES, BELTS AND WATCHBANDS SHOULD BE REMOVED AND DESTROYED.

EYE PROTECTION: USE CHEMICAL GOGGLES. IF VAPOR EXPOSURE CAUSES EYE IRRITATION, USE A FULL-FACE RESPIRATOR. EYE WASH FOUNTAIN SHOULD BE LOCATED IN IMMEDIATE WORK AREA.

9. ADDITIONAL INFORMATION

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

GROUND ALL TRANSFER EQUIPMENT. HOLD BULK STORAGE UNDER A NITROGEN BLANKET. THIS PRODUCT SHOULD NOT COME IN CONTACT WITH COPPER OR COPPER-BEARING ALLOYS. GOOD GENERAL HOUSEKEEPING PROCUDURES SHOULD BE FOLLOWED.

10. NFPA HAZARD RATING

4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT

HEALTH: 2
FIRE: 1
REACTIVITY: 0
SPECIFIC:

11. REGULATORY INFORMATION: STATUS ON SUBSTANCE LISTS

THE CONCENTRATIONS SHOWN IN THIS DOCUMENT ARE MAXIMUM OR CEILING LEVELS (WEIGHT %) TO BE USED FOR REGULATIONS. TRADE SECRETS ARE INDICATED BY "TS".

MATERIAL SAFETY DATA SHEET

MSDS

ECOPOXY HARDENER

PAGE 4

FEDERAL EPA

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (CERCLA)

REQUIRES NOTIFICATION OF THE NATIONAL RESPONSE CENTER OF RELEASE OF QUANTITIES OF HAZARDOUS SUBSTANCES EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITIES (RQ'S) IN 40 CFR 302.4. COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL WHICH COULD BE REQUIRE REPORTING UNDER THE STATUTE ARE:

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT	RQ
NONE			

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III

SECTIONS (301-304) REQUIRE EMERGENCY PLANNING BASED ON THRESHOLD PLANNING QUANTITIES (TPQ'S) AND RELEASE REPORTING BASED ON REPORTABLE QUANTITIES (RQ'S) IN 40 CFR 355. COMPONENTS PRESENT IN THIS PRODUCT AT A LEVEL WHICH COULD REQUIRE REPORTING UNDER THIS STATURE ARE:

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT
NONE		

SECTIONS (311-312) REQUIRE PRODUCTS BE REVIEWED AND APPLICABLE EPA HAZARD DEFINITIONS BE IDENTIFIED AND MADE KNOWN.

EPA HAZZARD CLASSIFICATIONS

ACUTE HAZARD	CHRONIC HAZARD	FIRE HAZARD	PRESSURE HAZARD	REACTIVE HAZARD
YES	YES	NO	NO	NO

SECTION (313) REQUIRES SUBMISSION OF ANNUAL REPORTS OF RELEASE OF TOXIC CHEMICALS THAT APPEAR IN 40 CFR 371 (FOR SARA 313). THIS INFORMATION MUST BE INCLUDED IN ALL MSDS'S THAT ARE DISTRIBUTED FOR THIS MATERIAL. COMPONENTS PRESENT IN THIS PRODUCT AT LEVEL WHICH COULD REQUIRE REPORTING UNDER THE STATUE ARE:

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT
NONE		

IF YOU ARE UNSURE IF YOU MUST REPORT MORE INFORMATION, CALL THE EPA EMERGENCY PLANNING AND RIGHT-TO-KNOW HOT LINE: 1-800-535-0202 OR 1-202-479-2449.

TOXIC SUBSTANCES CONTROL ACT (TCSA)

THE COMPONENTS OF THIS PRODUCT ARE CONTAINED ON THE CHEMICAL SUBSTANCE INVENTORY LIST.

OTHER REGULATORY INFORMATION

D.O.T. SHIPPING NAME: AMINES, LIQUID, CORROSIVE, N.O.S. CLASS 8, UN 1760 PG III
CONTAINS ISOPHORONEDIAMINE

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY EXPRESSED OR IMPLIED IS MADE. MANUFACTURER URGES SUPPLIERS AND USERS OF THIS PRODUCT TO EVALUATE IT'S SUITABILITY AND COMPLIANCE WITH LOCAL REGULATION.