


# Specifications Douglas-fir Flooring:

## Solid Plank Classic Fir

<b>Product</b>	<b>Classic Douglas-fir</b>	
<b>Species</b>	<i>Pseudotsuga menziesii</i>	
<b>Grain Pattern</b>	Clear tight, vertical grain	
<b>Color Tones</b>	Initially a light beige, this floor develops a into a golden cognac color; unique only to Douglas fir.	
<b>Product Description</b>	Classic Douglas-fir is made without compromise for the fir aficionado. This exquisite material is selectively harvested from the coast of British Columbia. We use only sap-restricted lumber to ensure that this floor has a consistent and bold, uniform look. Sapwood is the lighter yellow colored streaking common to fir. The combination of a wider plank, long lengths and tight consistent grain create a fir floor like no other.	
<b>Finish</b>	Unfinished.	
<b>Millwork</b>	Square edge, unmatched ends.	
<b>Dimensions</b>	Standard dimensions: 3/4" thick X 4 1/4" face width X random lengths 4' to 10' Non standard dimensions available upon request.	
<b>Density/Hardness</b>	Hardness rating of 710 Janka.	
<b>Packaging</b>	Bulk lift.	
<b>Lead Time</b>	2 to 3 weeks.	
<b>Recommendations</b>	Nail down into subfloor or on stringers. Not recommended for installation on concrete or above radiant floors. Use our engineered flooring. Install per NWFA guidelines.	
<b>Other</b>	Custom sizes available 1/2" to 2" thick, 2" to 7 1/4" wide.	
<b>About These Specs</b>	This specification sheet is designed to give general information about our products. The specifications are subject to change and products are limited to material availability. Please contact us directly for the availability of this product and the particular specifications needed for your project. Detailed specifications will be confirmed in writing.	

### Contact Info

#### Address:

#5 10189 McDonald Pk. Rd.  
Sidney, BC, V8L 3S8, Canada


#### Phone: 1-800-667-2275 , Fax: (250) 656 9663

**Email:** [flooring@westwindhardwood.com](mailto:flooring@westwindhardwood.com)

**Web:** <http://www.flooringbywestwindhardwood.com>

# Specifications Douglas-fir Flooring:

## Solid Plank New Fir

<b>Product</b>	<b>New Fir</b>	
<b>Species</b>	<i>Pseudotsuga menziesii</i>	
<b>Grain Pattern</b>	Course Vertical Grain with the odd knot.	
<b>Color Tones</b>	Amber heartwood contrasted with yellow/tan sapwood	
<b>Product Description</b>	A fresh new option, produced from second growth lumber; harvested from younger sustainable forests. Like a young wine, it is more lively and wild; offering a distinctive grain pattern, accented by lighter toned sapwood. New Fir will add warmth, charm and interest to any décor.	
<b>Finish</b>	Unfinished.	
<b>Millwork</b>	Square edge, unmatched ends.	
<b>Dimensions</b>	Standard dimensions: 3/4" thick X 4 1/4" face width X random lengths 4' to 10' Non standard dimensions available upon request.	
<b>Density/Hardness</b>	Hardness rating of 710 Janka.	
<b>Packaging</b>	Bulk lift.	
<b>Lead Time</b>	2 to 3 weeks/	
<b>Recommendations</b>	Nail down into subfloor or on stringers. Not recommended for installation on concrete or above radiant floors. Use our engineered flooring. Install per NWFA guidelines.	
<b>Other</b>	Custom sizes available 1/2" to 2" thick, 2" to 7 1/4" wide.	
<b>About These Specs</b>	This specification sheet is designed to give general information about our products. The specifications are subject to change and products are limited to material availability. Please contact us directly for the availability of this product and the particular specifications needed for your project. Detailed specifications will be confirmed in writing.	

### Contact Info


#### Address:

#5 10189 McDonald Pk. Rd.  
Sidney, BC, V8L 3S8, Canada

#### Phone: 1-800-667-2275 , Fax: (250) 656 9663

**Email:** [flooring@westwindhardwood.com](mailto:flooring@westwindhardwood.com)

**Web:** <http://www.flooringbywestwindhardwood.com>

<b>Product</b>	<b>Recycled Fir – FSC Recycled</b>	
<b>Species</b>	<i>Pseudotsuga menziesii</i>	
<b>Grain Pattern</b>	Mixed grain, knots and visible signs of distress	
<b>Color Tones</b>	Mainly amber with some tan/yellow sap wood.	
<b>Product Description</b>	<p>Our commitment to the environment shines with our FSC Recycled Douglas-fir flooring. Using beams from dismantled buildings and mature structures, a mix of grain patterns is achieved, each telling its own story. Whether working on a LEED project, or simply reducing your environmental footprint, recycled fir is a feel good choice.</p> <p>*Current recycled stock is from laminated industrial beams, perpendicular glue lines are visible (can be cut out if desired), occasional aluminum nails may be found.</p>	
<b>Finish</b>	Unfinished.	
<b>Millwork</b>	Square edge, unmatched ends.	
<b>Dimensions</b>	Standard dimensions: 3/4" thick X 4 1/4" face width X random lengths 4' to 10' Non standard dimensions available upon request.	
<b>Density/Hardness</b>	Hardness rating of 710 Janka	
<b>Packaging</b>	Bulk lift.	
<b>Lead Time</b>	2 to 4 weeks	
<b>Recommendations</b>	Nail down into subfloor or on stringers. Not recommended for installation on concrete or above radiant floors. Use our engineered flooring. Install per NWFA guidelines.	
<b>Other</b>	Custom sizes available 1/2" to 2" thick, 2" to 7 1/4" wide.	
<b>About These Specs</b>	This specification sheet is designed to give general information about our products. The specifications are subject to change and products are limited to material availability. Please contact us directly for the availability of this product and the particular specifications needed for your project. Detailed specifications will be confirmed in writing.	

<b>Contact Info</b>	<p><b>Address:</b> #5 10189 McDonald Pk. Rd. Sidney, BC, V8L 3S8, Canada</p> <p><b>Phone:</b> 1-800-667-2275 , Fax: (250) 656 9663</p> <p><b>Email:</b> <a href="mailto:flooring@westwindhardwood.com">flooring@westwindhardwood.com</a></p> <p><b>Web:</b> <a href="http://www.flooringbywestwindhardwood.com">http://www.flooringbywestwindhardwood.com</a></p>
---------------------	---

<b>Product</b>	<b>Appearance Fir – FSC Pure</b>	
<b>Species</b>	<i>Pseudotsuga menziesii</i>	
<b>Grain Pattern</b>	Vertical, fine to medium grain, with tight knots	
<b>Color Tones</b>	Amber tone with occasional sap streaking	
<b>Product Description</b>	A uniquely warm look with a touch of rustic charm. This Douglas-fir floor is harvested according to FSC standards in the mountains of North-Eastern BC. The high altitude growing conditions contribute to finer than normal grain which is contrasted nicely by tight knots. A unique and responsibly harvested floor.	
<b>Finish</b>	Unfinished.	
<b>Millwork</b>	Square edge, unmatched ends.	
<b>Dimensions</b>	Standard dimensions: 3/4" thick X 4 1/4" face width X random lengths 4' to 10' Non standard dimensions available upon request.	
<b>Density/Hardness</b>	Hardness rating of 660 Janka	
<b>Packaging</b>	Bulk lift.	
<b>Lead Time</b>	8- 10 weeks, possibly longer depending on material availability	
<b>Recommendations</b>	Nail down into subfloor or on stringers. Not recommended for installation on concrete or above radiant floors. Use our engineered flooring. Install per NWFA guidelines.	
<b>Other</b>	Custom sizes available 1/2" to 2" thick, 2" to 7 1/4" wide.	
<b>About These Specs</b>	This specification sheet is designed to give general information about our products. The specifications are subject to change and products are limited to material availability. Please contact us directly for the availability of this product and the particular specifications needed for your project. Detailed specifications will be confirmed in writing.	

<b>Contact Info</b>	<b>Address:</b> #5 10189 McDonald Pk. Rd. Sidney, BC, V8L 3S8, Canada	<b>Phone:</b> 1-800-667-2275 , Fax: (250) 656 9663 <b>Email:</b> flooring@westwindhardwood.com <b>Web:</b> <a href="http://www.flooringbywestwindhardwood.com">http://www.flooringbywestwindhardwood.com</a>
---------------------	---	--