



## General information

Depending on the intensity of use, a floor's finish is subject to a natural wearout. Therefore, regular care is absolutely necessary. If the surface shows damages due to heavy wear, it must be sanded and reimpregnated. Wood is a natural product. It permanently changes its volume and adjusts to the room's humidity. During the time of heating, the relative humidity decreases significantly. The wood reacts to this situation by emitting its own moisture so that it starts to contract. This process is visually recognizable by gap forming in the parquet floor. The longer and the more intensely you heat your rooms, the dryer becomes the air and the more gaps are forming. The widest gaps are mostly to be expected towards the end of the heating period. At the end of summer they are generally a lot smaller or closed again. In order to counteract gap forming, you may, for instance, hang humidifiers to your radiators and/or have an adequate amount of plants in your house.

- Leave your freshly impregnated floor at least 2-3 days time until you start straining or caring it.
- Do not use steel wool or sharp cleaning pads. Dirt and sand can be like sandpaper on your floor and have to be removed immediately.
- For cleaning and care you should only use high-quality and products matching each other.
- By defining large dirt collecting areas in front of the entrance you can achieve an effective reduction of dirt on your floors.
- In order to avoid scratches, you may put pieces of felt under your seating furniture. If you have furniture with rollers, the floor should be protected with mats.

Your wooden floor was impregnated on the \_\_\_\_\_

with: \_\_\_\_\_

Dealer / Signature:

**Oli Lacke GmbH**

Bahnhofstr. 22 | 09244 Lichtenau, Germany  
Tel. +49 (0) 37208/84-0 | Fax +49 (0) 37208/84-382  
info@oli-lacke.de | www.oli-lacke.de



## Care of oil / wax treated wooden floors



DE\_Pflegeanweisung für öl-/wachsbehandelte Holzfußböden\_ST\_28072015



## OLI-NATURA Wood soap

NATURAL WOOD SOAP FOR THE MAINTENANCE CLEANING OF ALL OILED AND WAXED WOODEN, PARQUET AND CORK SURFACES



OLI-NATURA Wood Soap is a gentle soap-based cleaning concentrate for regular wiping care of all oil and wax treated wooden and cork floors in the interior. With this soap, floors can be cleaned easily and thoroughly without causing damage to the surface.

### Maintenance cleaning

Maintenance cleaning is to be understood as a regular cleaning of the floor, which includes dry cleaning by broom and vacuum cleaner, but also wiping the floor.

Commonly dirty floors in living areas should be wiped slightly damp with OLI-NATURA Wood soap (50 ml per 10 litres of water) at least once a month or whenever necessary with a wrung-out mop or cloth according to the instructions on the bottle.

In business areas the intervals are shorter so that the floors should be wiped at least once a week. You ought to avoid stagnant wetness in order to prevent a swelling up at joints and gaps. Persistent stains can be treated with pure OLI-NATURA wood soap and can be removed with a wet cloth after a few minutes' absorption time.



Technical Data

Scan QR-Code



## OLI-NATURA Wood care oil

NATURAL WOOD CARE OIL FOR THE RECONDITIONING OF OILED WOOD, PARQUET AND CORK SURFACES



OLI-NATURA Care Oil is a deeply penetrating, quick drying oil for the reconditioning and care of naturally oiled wood, parquet and cork surfaces. It is both a cleaner and care product, and gives worn-out oiled surfaces back their beauty and brilliance. Factory-oiled parquet flooring obtains an additional protection against moisture at edges and joints. Besides an unpigmented natural

version, OLI-NATURA Wood Care Oil is also available in white for the reconditioning of surfaces oiled in white or grey.

### Reconditioning and restoration

The necessity for a floor's reconditioning depends on its exposure to wear. In order to preserve the character of an oiled floor, we recommend the treatment of high-traffic oiled surfaces with our deeply penetrating, fast drying OLI-NATURA Wood Care Oil. Apply the oil very thinly on the thoroughly cleaned floor. Then polish it, using a cotton cloth on small areas or a burnisher with white pad on larger ones. In case of highly worn-out surfaces, you should allow a residence time of 10 to max. 60 minutes before polishing. Besides an uncoloured natural version, OLI-NATURA Care Oil is also available in white for the reconditioning of white and grey oiled floors.



Technical Data

Scan QR-Code



## OLI-AQUA CLEAN 15.97 | Basic parquet cleaner

MILD BASIC CLEANER FOR ALL WATERPROOF SEALED AND OILED WOOD, PARQUET AND CORK FLOORS



Mild detergent for post-construction cleaning as well as for heavily soiled wood and parquet floors for which common wipe care products are not sufficient anymore. Removes old cleaner residues and polymer films reliably.

### Basic cleaning

A basic cleaning is always to be carried out on the entire area of the floor and becomes necessary when unsightly coats have deposited or heavy dirt cannot be removed by common maintenance cleaning anymore. For basic cleaning we recommend an application of our OLI-AQUA CLEAN parquet floor basic cleaner, diluted with water at a ratio of 1:1 - 1:3, with a broad floor wiper. Avoid puddle formation.

Allow the cleaner to work in for a short while and if necessary, loosen dirt and care product residues by scrubbing. Wipe up the dirt layer immediately afterwards with an absorbent, dry mop from smaller areas or with a water hoover from larger ones. Then wipe the floor again slightly damp with clear water. A basic cleaning should be done as seldom as possible and by a specialist.



Technical Data

Scan QR-Code