



OLI-NATURA Hardwax oil

OIL-WAX COMBINATION FOR THE BASIC TREATMENT OF WOOD, CORK AND OSB FLOORING AS WELL AS FOR STAIRS, DOORS AND WORKTOPS IN THE INTERIOR.

A true classic: OLI-NATURA Hardwax oil is made of vegetable oils, waxes and resins, and combines the deep impregnating effect of an oil with the surface protection of a wax. Easy application by hand and machine; two coats are necessary. Due to its proportion of wax it is polishable and slightly higher in gloss with a 'greasier' touch than purely oiled surfaces. Suitable for all applications in the interior.

Properties and test standards:

- Giscode Ö60
- EU – Decopaint Directive
- DIN 71-3 (safety of toys)
- DIN 53160 (saliva and sweat proof)
- Free of formaldehyde and aromatic compounds
- Without biocidal substances and preservatives

Ordering Code: uncoloured, silk matt (A02687), in RAL colours

Packaging: 3, 1 l

Composition: Modified plant oils and waxes, such as linseed oil, tung oil and carnauba wax; disaromatized hydrocarbons; lead-free drying agents.

Shelf-life: 12 months in factory sealed containers. Storage and transport temperature: below +30°C / above +5°C.

Labelling: For labelling details and safety instructions, please refer to our safety datasheet at www.oli-lacke.de.

Consumption: 2 coats | 40-50 g/sqm per coat (20-25 sqm/l), depending on the absorptivity of the surface

Tools: Mohair roller, oil brush or flat brush, white pad

Handling instructions:

- Optimum processing conditions are: +20°C and 50% relative humidity.
- Do not use at temperatures below +15°C.
- Apply material at room temperature and shake well before use!
- Always apply to a test area before application on veneers, and on exotic woods that are rich in active substances!
- Danger of spontaneous combustion! Clean contaminated cloths / pads immediately after use or submerge in water.
- Mix containers with different batch numbers before use to avoid colour differences.
- Remove excess oil from the surface to avoid puddle formation.

Surface preparation:

- Sand the wood surface thoroughly; start with coarse grit, final sanding for flooring with grit 100-150, for furniture with grit 150-240.
- The surface must be dry, thoroughly cleaned and free of oil, wax, grease, silicon and sanding dust.
- For parquet floors we recommend you to fill the joints with OLI-Fugenkitt joint filler solution and sanding dust before the final sanding.

Setup recommendations:

- Stir oil well. Work in sections of 5-10 sqm. Pour oil on the surface (40-50 g/sqm depending on the type of wood) and immediately distribute evenly and thinly with a brush, mohair roller, or flat brush.
- After a residence time of 20-30 minutes, work the oil in with a white pad by hand or rotary machine until the surface appears uniformly matt.
- After 6-8 hours, repeat the procedure as described above.
- Depending on the humidity and temperature, the oiled surface will be fully wear-resistant after 2-3 days. Protect it from water during this time.

After-treatment and care:

For regular maintenance cleaning we recommend OLI-NATURA Wood Soap.

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Last update: 13.07.2015 / AS

