



OLI-NATURA Project oil

MEDIUM-SOLID OIL FOR THE UNIVERSAL BASIC TREATMENT AND CARE OF FURNITURE SURFACES, WOODEN FLOORS, STAIRS, AND FOR WETROOMS.

OLI-NATURA Project Oil is our universal natural oil with 60% solids which was designed for an easy application also by hand. Due to its excellent auto-penetration, Project Oil is suitable for the impregnation of larger surfaces, such as parquet floors and worktops, but also for furniture and floorboards with chamfers that are normally difficult to coat or oil. One of the oil's main characteristics is its excellent protection against water without compromising the wood's important function of moisture regulation. Project Oil is available in 7 transparent and intermixable wood colours. An overcoating with the two-component OLI-AQUA TOP 51.20 parquet floor sealer is possible.

Properties and test standards:

- Giscode Ö60
- EU – Decopaint Directive
- Z-157.10- 18 (low-emission; certified construction product in accordance with DIBt standards)
- DIN 71-3 (safety of toys)
- DIN 53160 (saliva and sweat proof)
- Free of formaldehyde and aromatic compounds
- Without biocidal substances and preservatives

Ordering Code: Nature/uncoloured (A01370), Lime white (A01371), Grey (A01372), Teak (A01373), Mahogany (A01374), Walnut (A01390), Padouk (A01391), Wenge (A01392), Project oil spray nature (A02204)

Packaging: 10, 3, 1 l

Composition: Modified plant oils such as linseed oil; isoparaffinic hydrocarbon of pharmaceutical quality; lead-free drying agents.

Shelf-life: 24 months in factory sealed containers. Storage and transport temperature: below +30°C / above +5°C.

Labelling: For labelling details and safety instructions, please refer to our safety datasheet at www.oli-lacke.de.

Consumption: 1-2 coats | 40-50 g/sqm per coat (20-25 sqm/l), depending on the absorptivity of the surface

Tools: Mohair roller, oil brush or flat brush, green pad, white pad

Handling instructions:

- Optimum processing conditions are: +20°C and 50% relative humidity.
- Do not use at temperatures below +15°C.
- Apply material at room temperature and shake well before use!
- Always apply to a test area before application on veneers, and on exotic woods that are rich in active substances!
- Danger of spontaneous combustion! Clean contaminated cloths / pads immediately after use or submerge in water.
- Mix containers with different batch numbers before use to avoid colour differences.
- Remove excess oil from the surface to avoid puddle formation.
- As a priming oil: overcoatable with OLI-AQUA TOP 51.20 | 2c parquet floor sealer after overnight drying (48 hours for color oils). Slightly roughen the surface before overcoating with a rotary disc machine and a green pad.
- Application by spraying and dipping possible.
- Do not use in spray facilities together with NC lacquers.

Surface preparation:

- Sand the wood surface thoroughly; start with coarse grit, final sanding for flooring with grit 100-150, for furniture with grit 150-240.
- The surface must be dry, thoroughly cleaned and free of oil, wax, grease, silicon and sanding dust.
- For parquet floors we recommend you to fill the joints with OLI-Fugenkitt joint filler solution and sanding dust before the final sanding.

Setup recommendations:

- Stir oil well. Work in sections of 5-10 sqm. Pour oil on the surface (40-50 g/sqm depending on the type of wood) and immediately distribute evenly and thinly with a brush, mohair roller, or flat brush.
- After a residence time of 20-30 minutes, work the oil in with a green pad by hand or rotary machine until the surface appears uniformly matt.
- Final polish after another 4-6 hours by hand using a cotton cloth or white pad and rotary machine.
- Depending on the humidity and temperature, the oiled surface will be fully wear-resistant after 2-3 days. Protect it from water during this time.

After-treatment and care:

Use OLI-NATURA Wood Care Oil for reconditioning and care. For regular maintenance cleaning we recommend OLI-NATURA Wood Soap.

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Last update: 13.07.2015 / AS

