



## OLI-NATURA Yacht & Teak oil

WEATHERPROOF HARDWOOD OIL WITH UV PROTECTION FOR THE BASIC TREATMENT AND CARE OF YACHT DECKS, TERRACES AND GARDEN FURNITURE

OLI-NATURA Yacht & Teak Oil is a universal oil for exterior applications with a highly effective long-term UV protection especially for the weatherproof basic treatment and care of yacht decks, terraces, pool surroundings and garden furniture made of hardwood and exotic wood as well as for pressure-impregnated softwood. The oil produces a hardwearing surface and highlights the natural colour and grain of the wood. The product is easy to apply and penetrates deeply. The oil blocks UV light effectively and protects the wood from turning grey or brittle.

### Properties and test standards:

- EU – Decopaint Directive
- DIN 71-3 (safety of toys)
- DIN 53160 (saliva and sweat proof)
- Free of formaldehyde and aromatic compounds
- Without biocidal substances and preservatives

**Ordering Code:** Nature/uncoloured (A01397), Teak (A01398), Silver grey (A01399)

**Packaging:** 3, 1 l

**Composition:** Modified plant oils such as linseed oil; isoparaffinic hydrocarbon of pharmaceutical quality; lead-free drying agents, lightfast soil and mineral pigments, micronised titan oxide.

**Shelf-life:** 24 months in factory sealed containers. Storage and transport temperature: below +30°C / above +5°C.

**Labelling:** For labelling details and safety instructions, please refer to our safety datasheet at [www.oli-lacke.de](http://www.oli-lacke.de).

**Consumption:** 1-2 coats | 40-80 g/sqm per coat (12-25 sqm/l), depending on the absorptivity of the surface

**Tools:** Mohair roller, oil brush or cotton cloth, white pad

### Handling instructions:

- Do not use at temperatures below +15°C
- Shake well before use!
- Do not apply in damp weather or under direct sunlight.
- Danger of spontaneous combustion! Clean contaminated cloths / pads immediately after use or submerge in water.
- Mix containers with different batch numbers before use to avoid colour differences.
- Remove excess oil from the surface to avoid puddle formation.

### Surface preparation:

- The wood must be clean, dry and free of grease. If the wood is heavily soiled, we recommend first cleaning with OLI-NATURA Wood Outdoor Cleaner. If necessary, sand back rising wood fibres and rough spots with fine sandpaper (grit 220).

### Setup recommendations:

- Stir oil well. Work in sections of 5-10 sqm. Pour oil on the surface (40-80 g/sqm depending on the type of wood) and immediately distribute evenly and thinly in the direction of the wood grain.
- Polish with a white pad by hand after a residence time of 20-30 min.
- If the wood is highly desiccated, repeat the application as described above.
- Depending on the weather, dust-dry in 1-2 hours and fully cured in 2-3 days.

### After-treatment and care:

Use OLI-NATURA Yacht & Teak Oil for reconditioning and care twice a year or as required. For maintenance cleaning we recommend OLI-NATURA Wood Outdoor Cleaner.

Our verbal and written recommendations for application can only provide non-binding advice. They are based on our experiences and the current state of knowledge with regard to practical use. These recommendations, however, do not release the user from the obligation to test the suitability of the product for the intended purpose and application himself. This statement supersedes all previous versions. Last update: 13.07.2015 / AS

